



Notes.

In plan view this shows the footprint that a 750mm BE113 kit 3 and 1000mm BE113 kit 4 will cover. E.G. BE113 kit 3 has a max. diameter of 1.7m with BE113 kit 4 has a max. diameter of 2.2m

Minimum mast to wall clearance is, Kit 3 420mm & Kit 4 540mm.

All legs have a 16mm hole to allow ground stakes as per BE508 or BE509.

Steel loops are at the end of each leg for guy lines and tensioners to aid support.

Standard guys are recommended at one third the distance from the base of the mast to its height.

This can be increased with guys at every diameter change for the telescopic masts when a light load is required to be supported. (Situations change when in open country or hostile areas and or severe weather conditions)

This system can fully set up along the ground to the height required and walked up with just the final tensioning to get the mast vertical.

BE620-T-Kit guy ring set for all the telescopic masts.

BARENCO Ltd.

DRAWN Name		BPG		Footprint for BE113 Kit 3 & 4	
Dimensions: mm					
Date	14/11/2022	SIZE	DWG NUMBER		
Last Rev.		A4	BE113 Kit 3 & 4		
SCALE 5 : 1		REV -	SHEET 1 OF 1		

Barenco Ltd

14, Winterbeck Industrial Estate, Orston Lane, Bottesford, Nottingham, NG13 0AU
 Email : sales@barenco.co.uk Web address : www.barenco.co.uk Tel : 0(44)1949 860400