



**Packing List.**

- One base plate with hinge attached and positioned for final assembly.
- One top double socket.
- One gin pole cap.
- Four ground spikes.

To assemble for the first time.

Remove the 4 off M10 x 25mm bolts and washers on top of hinge plate. Place top double socket for mast and gin pole on top of hinge plate, ensure on assembly that fixed stud is positioned farthest from hinge bolts on base hinge. The remaining 3 off M8 x 20mm bolts complete the double socket mounting to the hinge plate. Replace the 4 off M10 x 25mm bolts from the position they came from, these are the only bolts that need removing to tilt the mast when unit is in operation. Hinge bolts can be adjusted to suit friction required when operating.

The finish to this bracket is Sherardized.

<b>BARENCO Ltd.</b>			
DRAWN Name	B. Gell	<b>BE103 Assembly</b>	
Dimensions: mm			
Date	15/10/2019	SIZE	DWG NUMBER
Last Rev.		<b>A4</b>	<b>BE103</b>
SCALE 5:1		REV -	SHEET 1 OF 1

**Barenco Ltd**  
 14, Winterbeck Industrial Estate, Orston Lane, Bottesford, Nottingham, NG13 0AU  
 Email : Sales@barenco.co.uk Web address : www.barenco.co.uk Tel : 01949 860400