



End profile of
centre section



4 Way guy clamp connected to support arms with M12 x 30mm Hex set, flat washers and M12 self locking nut. Ensure all legs have contact with the surface by pushing down the guy clamp before securing to mast.

A

180mm high socket 60.3mm O.D. will except 2" diameter masts or scaffold 48.3mm. Other options are available.

90 degree twist in arm

Bolt through to captive nut on back plate with M10 x 25mm Hex set & flat washer x 4

To fit external guy kit remove original bolt and fit link with M10 x 30mm Hex set. Guy kit sold separately

Section A

Bolt through end rail and support arm with M10 x 25mm Hex set and flat washer x 4

Notes.

BE106/450 Requires 4 x 450mm x 450mm x 32mm slabs gives approx 56Kg of ballast.

BE106/600 Requires 4 x 600mm x 600mm x 50mm slabs gives approx 160Kg of ballast.

Do not load slabs until all assembly work and leveling is complete and all bolts locked off.

Barenco Ltd

14, Winterbeck Industrial Estate, Orston Lane, Bottesford, Nottinghamshire. NG13 0AU
Email : sales@barenco.co.uk. Web address : www.barenco.co.uk Tel : 01949 860400

BARENCO Ltd.

DRAWN Name	B. Gell	450mm & 600mm Flat roof mount General Assembly	
Dimensions: mm		SIZE	DWG NUMBER
Date	17/04/2019	A4	0000-0000
Last Rev.		REV -	SHEET 1 OF 1
SCALE 1 : 1			